


water supply and drain connection kit

linea mini & gs3



la marzocco

handmade in florence

linea mini & gs3

Water Supply Connection V1.0 - 07/2015



la marzocco

handmade in florence

Chapters

- 1. Water Supply Connection Assembly linea mini page 3
- 2. Water Supply Connection Assembly gs3 page 4
- 3. Hole on the Counter linea mini page 5
- 4. Hole on the Counter gs3 page 6
- 5. Water Supply Connection Instructions linea mini page 7
- 6. Water Supply Connection Instructions gs3 page 14



La Marzocco S.r.l.

Via La Torre 14/H
Località La Torre
50038 Scarperia e San Piero
(Florence) - ITALY

www.lamarzocco.com
info@lamarzocco.com

T: +39 055 849 191
F: +39 055 849 1990

1. Water Supply Connection Assembly




Item	Part number	Description
1	911	PLUMBING CONNECTION KIT LINEA MINI CE
2	C.1.223	CONTACT BY PASS PLATE
3	VITE3X8	3X8 S/S SCREW
4	I.1.062	VITE AUT 3.5X13 TC TCR INOX
5	L308	CLEAR ARMOURED DRAIN HOSE
6	L312	HOSE CLAMP
7	F.8.003	HOSE CONNECTOR QUICK CONNECTION
8	H.1.010.01	ORING 3087 (2-118) EPDM 70 SHA
9	F.8.002	DISCHARGE FITTING QUICK CONNECTION
10	L325	150CM S/S BRAIDED HOSE, G3/8-G1/4 GS3


Item	Part number	Description
1	912	PLUMBING CONNECTION KIT LINEA MINI ETL *
2	C.1.223	CONTACT BY PASS PLATE
3	VITE3X8	3X8 S/S SCREW
4	I.1.062	VITE AUT 3.5X13 TC TCR INOX
5	L308	CLEAR ARMOURED DRAIN HOSE
6	L312	HOSE CLAMP
7	F.8.003	HOSE CONNECTOR QUICK CONNECTION
8	H.1.010.01	ORING 3087 (2-118) EPDM 70 SHA
9	F.8.002	DISCHARGE FITTING QUICK CONNECTION
10	L326	150CM S/S BR.HOSE, 3/8" COMPR.-G1/4

* This kit is for North America only

2. Water Supply Connection Assembly




1	913	PLUMBING CONNECTION KIT GS3 CE
2	L308	CLEAR ARMoured DRAIN HOSE
3	L312	HOSE CLAMP
4	F.8.003	HOSE CONNECTOR QUICK CONNECTION
5	H.1.010.01	ORING 3087 (2-118) EPDM 70 SHA
6	F.8.002	DISCHARGE FITTING QUICK CONNECTION
7	L325	150CM S/S BRAIDED HOSE, G3/8-G1/4 GS3
Item	Part number	Description



1	914	PLUMBING CONNECTION KIT GS3 ETL
2	L308	CLEAR ARMoured DRAIN HOSE
3	L312	HOSE CLAMP
4	F.8.003	HOSE CONNECTOR QUICK CONNECTION
5	H.1.010.01	ORING 3087 (2-118) EPDM 70 SHA
6	F.8.002	DISCHARGE FITTING QUICK CONNECTION
7	L326	150CM S/S BR.HOSE, 3/8" COMPR.-G1/4
Item	Part number	Description


* This kit is for North America only

3. Hole on the Counter






WARNING
If the above-mentioned instructions are not adhered to the manufacturer cannot be held responsible for damage to persons or things.

4. Hole on the Counter



▲ WARNING ▲
 If the above-mentioned instructions are not adhered to the manufacturer cannot be held responsible for damage to persons or things.





5. Water Supply Connection Instructions







▲ WARNING ▲
Hazardous voltage disconnect from power supply before servicing.

▲ WARNING ▲
The integrated brew group and steam boiler contain water at elevated temperature. Water temperature over 125°F / 52°C can cause severe burns instantly or death from scalding (integrated brew group 200°F/93.3°C - steam boiler 260°F / 127°C).





5. Water Supply Connection Instructions







5. Water Supply Connection Instructions







5. Water Supply Connection Instructions





5. Water Supply Connection Instructions



5. Water Supply Connection Instructions




5. Water Supply Connection Instructions



6. Water Supply Connection Instructions


1.




▲ WARNING ▲
Hazardous voltage disconnect from power supply before servicing.

▲ WARNING ▲
The integrated brew group and steam boiler contain water at elevated temperature. Water temperature over 125°F / 52°C can cause severe burns instantly or death from scalding (integrated brew group 200°F/93.3°C - steam boiler 260°F / 127°C).





2.



3.




6. Water Supply Connection Instructions




6. Water Supply Connection Instructions


8.




9.



10.



11.



6. Water Supply Connection Instructions

